

Aslon® Demarcation tiles

Material composition

Recycled rubber granulate bound with PU binder and provided with yellow EPDM marking strips.

Dimensions and thicknesses

Sizetolerance


Dimension: 1.200 mm x 600 mm

±2%

Thickness: 30 mm

±5%

Colour



Black with yellow lines > see different types of the demarcation tiles on page 2

Weight

14,5 kg

Density

800 kg/m³

Water permeable

920 mm/uur EN12616

Granulate

Standard 1 - 3 mm

Fire resistance

Efl to EN 13501

Smoke resistance

S2

Insulation value


Rd 0,15 EN13165 | U 3,13 EN 6946

Noise reduction

ΔLw 25 DB

Warranty

3 year warranty for wear resistance when used on a roof.
The warranty does not apply to colour.

WATER
PERMEABLESHOCK
ABSORBING

SUSTAINABLE





2 lines >
short side



1 line >
short side



2 lines >
long side



1 line >
long side



1 square >
bottom right



T-shape



U-shape



C-shape



L-shape >
upper left



L-shape >
upper right



Corner right



Corner left



1 line short side
square >
bottom right



1 line short side
square >
bottom left



1 square >
bottom left

Subject to change. This release replaces all previous versions. Version: 01-01-2025