

# Aslon® UniTRACK

## Garens

Materiaal:	PE monofilament	
Garen type:	9.000/8 Dtex PE.	(±5%)
Gewicht:	1.104 gr/m <sup>2</sup>	(±10%)

## Tufting

Tuftdeling:	tufted 3/8" Gauge	
Hoogte:	12 mm	(±10%)
Aantal steken:	30 cm <sup>1</sup>	(±10%)
	31.500 m <sup>2</sup>	(±10%)

## Primary backing

Backing:	100% PP Woven + Fleece, 135 gr/m <sup>2</sup> (10%)	
Gewicht:	135 gr/m <sup>2</sup>	

## Backing

Backing:	(SBR) Latex compound	
Pool gewicht:	975 gr/m <sup>2</sup>	

## Eind product

Totale hoogte:	14 mm	(±10%)
Totale gewicht:	2.214 gr/m <sup>2</sup>	(±10%)
UV-stabiliteit:	DIN 53387 Standard (6000 Hrs) W.O.M.Test	
Brandklasse:	Efl	
Rookklasse:	S2	

## Afmetingen:

Breedte:	2 m   4 m	
Lengte:	Rol 2m > 10 m   15 m   20 m   25 m - Rol 4m > 25 m	

## Garantie

2 jaar tegen het uitvallen van het garen bij normaal gebruik en onderhoud.