

Instructions Aslon® rubber products instructions for processing rubber tiles and products.

Surface:

Make sure you have a flat subsurface. If the subsurface does not consist of concrete, please contact Aslon Rubber

Drainage:

All rubber tiles are permeable. Always ensure proper drainage underneath the rubber tiles. The tile being continuously under water should not affect the rubber's lifespan. The lifespan of the glue, however, could be shortened. When gluing the product, the drainage system should not be closed. Glue in the direction of the gutter or in the direction of the slope

Product features:

Rubber granulate products can have a size tolerance/effect of no more than 2% and a thickness tolerance of no more than 5%. Rubber granulate products are made from recycled rubber, which contains Carbon Black which could come out as a black colouring agent

Tools:

Use the right tool like a straight strip or ruler, coarse teeth handsaw or jigsaw (low-speed engine), Stanley knife or a similar knife. Never use angle grinders, crosscut saws or saw tables

Laying the product:

- Measure carefully (not too tight as tiles can expand due to moisture absorption and shrinking by weather influences)
- Keep the ruler or strip on the section you need
- Moisten the cutting edge of the knife
- Saw/cut the straight pieces using a handsaw, jigsaw or Stanley knife
- Preferably use a jigsaw for cutting patterns
- When processing artificial grass tiles please always note the arrows on the bottom of the tiles

Glueing:

- The processing temperature should be at least 8°C
- Glue all rubber tiles at the seams
- Glue the rubber tiles or mats to the grooves on the floor
- The space between the grooves which should not be glued may be no more than 8 cm
- Mats should be dry prior to gluing and should be glued together on a dry and dust-proof subsurface
- Glue in the direction of the gutter or along with the slope

Maintenance:

Vacuum, sweep

Scrubber or polishing/cleaning machine

High-pressure washer (do not use a dirt killer head)

Hand cleaning products (hard brushes and soap)

Note: cleaning agents are allowed, provided corrosive agents are avoided

Always wear/use the right protective gear when processing the products

If you need more information about cleaning products, please contact Aslon Rubber