

MATERIAL COMPOSITION:

Recycled granulate bound using a PU binding agent and possibly a colouring agent

SIZE:

sizes: 500 x 250 mm / 500 x 500 mm / 1.000 x 1.000 mm

thickness: 30 mm, 40 mm, 45 mm, 50 mm, 65 mm en 100 mm

Size tolerance

± 2%

± 5 %

COLOURS:

black

red

green

grey

sand



COLOURFASTNESS:

The product is not colourfast and the colour may change due to influences of the weather and walking on the rubbertiles

CARBON BLACK:

Carbon black is a black colouring agent which exists in every rubber tile and which can come out due to influences of the weather

QUICKLIME/CEMENT VEILING:

Due to weather influences and quicklime/cement veiling of the surrounding objects the tiles might develop a white efflorescence

GUARANTEE:

3 year guarantee for wear-resistance, when used on roof terraces, balconies and gardens. The guarantee does not apply to colour

WEIGHT:

18,4 kg/m²

DENSITY:

800 kg/m³

WATER PERMEABILITY:

920 mm/h EN 12616

FIRE RESISTANCE:

Efl to EN 13501

SMOKE RESISTANCE:

S2

INSULATION VALUE:

Rd 0,15 EN13165

U 3,13 EN 6946

