

**MATERIAL COMPOSITION :**

Recycled rubber granulate bonded with a cold cure PUR elastomer bonding agent

**SIZES AND THICKNESS:**

width: 1.050 mm and 1.250 mm  
thickness: 3 - 20 mm

size tolerance

± 2%  
± 5 %

**COLOURS:**

colour: black and black with 10% EPDM  
EPDM colour: grey, green, red, blue and yellow

colourfastness: the product is not colourfast and the colour may change due walking on the floor

carbon black: carbon black is a black colouring agent which exists in every rubber product and which can come out due to influences of the weather

**SPECIFICATIONS:**

density: 730 kg/m<sup>3</sup>, 930 kg/m<sup>3</sup> en 1.000 kg/m<sup>3</sup>

slip resistance: R10

fire classifications: Efl to EN 13501

smoke classifications: S2

isulation value: Rd 0,15 EN13165  
U 3,13 EN 6946

sound absorbency: ΔLw 25 DB

heat transfer coefficient: EN ISO 6946  
3,13 U[W/(m 2K)]

thermal coefficient: EN 13165  
0,156 λDW/mK

thermal resistance: EN 13165  
0.15 RD (m2K)/W

**GUARANTEE:**

3 year guarantee, when used for fitness purposes. The guarantee does not apply to colour.