

MATERIAL COMPOSITION:

Recycled granulate bound using a PU binding agent and possibly a colouring agent

SIZES:

Sizes: 1.000 x 500 mm
Thickness: 45 en 65 mm

Size tolerance
± 2%
± 5%

COLOURS:

black green

**COLOURFASTNESS:**

The product is not colourfast and the colour may change due to influences of the weather and walking on the rubbertiles

CARBON BLACK:

Carbon black is a black colouring agent which exists in every rubber tile and which can come out due to influences of the weather

QUICKLIME/CEMENT VEILING:

Due to weather influences and quicklime/cement veiling of the surrounding objects the tiles might develop a white efflorescence

GUARANTEE:

3 year guarantee for wear-resistance, when used on roof terraces, balconies and gardens. The guarantee does not apply to colour

DENSITY: 800 kg/m³

FIRE RESISTANCE: Efl to EN 13501

SMOKE RESISTANCE: S2

INSULATION VALUE: Rd 0,15 EN13165
U 3,13 EN 6946

FALL HEIGHTS HEAD INJURY CRITERION (HIC)

Aslon SBR tiles comply with the strictest standards for impact protection set by EN1177:2008 and EN 1177:2017.

Thicknesses	Fall heights
45 mm	2,00 meter
65 mm	2,10 meter

