

MATERIAL COMPOSITION:

Recycled granulate bound using a PU binding agent and possibly a colouring agent. The EPDM markings are no prints or stickers and are therefore permanently embedded in the rubber.

SIZE:

sizes: 500 x 500 mm / 1.000 x 1.000 mm
thickness: 15 mm, 20 mm en 30 mm flat and with studs.
30 mm, 40 mm en 45 mm with studs

Size tolerance

± 2%

± 5 %

COLOURS:

Colours on demand

COLOURFASTNESS:

The product is not colourfast and the colour may change due to influences of the weather and walking on the rubber tiles

CARBON BLACK:

Carbon black is a black colouring agent which exists in every rubber tile and which can come out due to influences of the weather

QUICKLIME/CEMENT VEILING:

Due to weather influences and quicklime/cement veiling of the surrounding objects the tiles might develop a white efflorescence

GUARANTEE:

3 year guarantee for wear-resistance, when used at gyms. The guarantee does not apply to colour

GRANULAT:

fine 0,7 - 1 mm
standard 1 - 3 mm

DENSITY:

900 kg/m³ en 1.000 kg/m³

WATER PERMEABILITY:

920 mm/h EN 12616

FIRE RESISTANCE:

Efl to EN 13501

SMOKE RESISTANCE:

S2

INSULATION VALUE:

Rd 0,15 EN13165
U 3,13 EN 6946

NOISE REDUCTION:

ΔLw 25 DB

